

# BEXY-CII series


*Super Productivity  
Super Stitch Quality*

小型机中体现出  
卓越的性能。

- Servo Motor Drive
- 3 USB Ports
- LAN Connector Standard
- Easier Lubrication
- 伺服马达驱动
- U盘3端口
- 标准设备LAN接口
- 筒易加油

Perfect model for a variety of order sizes.  
Compact, Fast & Reliable.

此刺绣机，具有操作简单、适应性广、耐久性强等特点。



USB Memory



MODEL  
BEXY-S1506CII

## Machine Specifications / Main Dimensions ■ 主要机械规格 / 机械尺寸

MODEL 机种 · 机头数	Embroidery Area (mm) 刺绣面积(毫米)	Needle Distance (mm) 机头间距(毫米)	Continuous Design (mm) 整匹布 · 连续花样(毫米)	Number of Needles 针数	Stitch Length (mm) 针幅(毫米)	Speed (rpm) 转速 (rpm)		Power Supply (V) 电源 (v)	Power Consumption (kw) 耗电量 (kw)	Dimensions (mm) 最大机械尺寸 (毫米)		
						(Tubular Frame) (框架)	(Cap Frame) (帽框)			L	W	H
BEXY-S1502CII	450×520/520	520	450×1040	15	0.1~12.7	200~1100	200~1000	1 φ 100~240 3 φ 200~415	0.8	2045	1245	1690
BEXY-S1504CII	450×380/380	380	450×1520							2385		
BEXY-S1506CII	450×520/520	520	450×2080			3085						
	450×380/380	380	450×2280			3145						
BEXY-S1508CII	450×520/520	520	450×3120	4125								
	450×380/380	380	450×3040	3905								
	450×520/520	520	450×4160	200~1000						5265		

Note 1 : The embroidery area indicated above allows for maximum pantograph movement. The frame used may restrict the actual embroidery field size.

注 1 : 上述刺绣面积、表示为框架的最大移动量、实际的刺绣面积由于使用的框架的不同、而有限制。

Note 2 : The sewing speed range is indicated above. Actual sewing speed should be adjusted for your embroidery application, i.e., stitch length, fabric used, etc.

注 2 : 上述的刺绣速度根据刺绣的振幅及布料的素材等状况不同而发生变化。

